

### **1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY UNDERTAKING**

#### 1.1 Product identifier

Product name 18-2-18

### **1.2** Relevant use of the product

Applications Fertilizer

### 1.3 Manufacturer, Importer or Responsible Party

Name	FERTI TECHNOLOGIES
Address	560, Chemin Rhéaume, C.P 129
	JOL 2JO
	Saint-Michel, Québec, Canada
Telephone	450 454-7521
Contact email	astpierre@fertitechno.com

#### **1.4 Emergency phone number**

Telephone

USA National Capital Poison Center: 1 800 222 1222

### 2. HAZARDS IDENTIFICATION

#### 2.1. The hazard classification of the chemical according to HCS 2012 (US-GHS)

	Acute oral to x 5 Skin Irrit. 2 Eye Irrit. 2A STOT SE 3 Carc. 1 STOT RE 1	H303 H316 H320 H335 H350 H372
2.2.	Danger symbols	
	<b>c</b> . <b>1</b>	
2.3.	Signal word	Danger
2.4.	Hazard statements	H303 May be harmful if swallowed H315 Causes skin irritation.
		H319 Causes serious eye irritation.
		H335 May cause respiratory irritation.
		H350 May cause cancer H372 May cause damage to organs (lungs) through prolonged or repeated
		exposure if inhaled.



2.5.	Precautionary	
	statements Prevention	P201 Obtain special instructions before use.
		P202 Do not handle until all safety precautions have been read and
		understood.
		P260 Do not breathe dust.
		P264 Wash hands thoroughly after handling.
		P270 Do not eat, drink or smoke when using this product.
		P271 Use only outdoors or in a well-ventilated area.
		P280 Wear protective gloves/protective clothing/eye protection/face
		protection.
	Response	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable
		for breathing.
		P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do. Continue rinsing.
		P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
		P330 Rinse mouth.
		P302+P352 IF ON SKIN: Wash with plenty of water.
		P362+P364 Take off contaminated clothing and wash it before reuse.
		P314 Get medical advice/attention if you feel unwell.
	Storage	P405 Store locked up.
	Disposal	P501 Dispose of contents/container according to local regulations.
2.6.	Description of any hazards not otherwise classified	Not applicable.
2.7.	% ingredient(s) with unknown acute	Not applicable.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

toxicity

Chemical name		CAS-Nr.	Concentration %
Potassium sulfate		7778-80-5	C = 36.0 %
	Dicyandiamine (60 % - 100 %)	461-58-5	
	Non-hazardous component (5 % - 10 %)	Proprietary	
UFLEXX	N-(n-butyl)-thiophos phoric triamide (1 % - 5 %)	94317-64-3	C = 29.4 %
	N-methyl-2-pyrrolidone	872-50-4	
	Non-hazardous dye	Proprietary	
Calcium	Limestone (>=80 - <=100%)	1317-65-3	C = 9.3 %
carbonate	Quartz (SiO <sub>2</sub> ) (20%)	14808-60-7	- C - 9.5 %



	Natural calcium carbonate magnesium (90 % - 95 %)	1317-65-3	
lime	Lignosulfonate (5 % - 10 %)		C = 9.1 %
	Humic acid	n/a	
	Carbamide, Carbonyldiamide, Carbamidic Acid) (97.5% - 99.7%)	57-13-6	
Urea	Alkalinity as ammonia (150 ppm max)	mixture	C = 8.9 %
mixture	Methylenediurea (0 % - 2.5 %)	13547-17-6	
	Biuret (0% -1.5%)	108-19-0	
	Monobasic ammonium phosphate (70 % - 90 %)	7722-76-1	C = 3.8 %
MAP	Ammonium sulfate (5.5 % - 7.5 %)	7783-20-2	C = 3.0 %
	Iron oxide (70 % - < 80 %)	1317-61-9	
Iron	Calcium sulfate (3 % - < 5 %) 7778-1		C = 2.0 %
sucrate	Other components below reportable levels (20 % - < 30 %)	n/a	
Oil Dri	Montmorillonite (90% - 93%)	1302-78-9	C = 1.5 %
	Quartz (7% - 10%)	14808-60-7	C = 1.5 %

## **4. FIRST AID MEASURES**

### 4.1 First Aid measures after Inhalation

Following inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided by a qualified operator. Get medical attention if irritation develops and persists.	
4.2 First Aid measures after Skin	exposure	
Following skin contact	Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Get medical attention if irritation develops and persists.	
4.3 First Aid measures after Eye exposure		
Following eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.	
4.4 First Aid measures after Inge	stion	
Following ingestion	Induce vomiting, but only if victim is fully conscious. Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Do not give milk or alcoholic beverages. Call a physician.	
4.5 Most important symptoms a	nd effects, both acute and delayed	
INHALATION	Respiratory irritation.	
SKIN	Skin irritation, redness,	
EYES	Causes serious eye irritation	
INGESTION	May be fatal if a large quantity has been ingested: Abdominal pain. Diarrhea. Nausea. Vomiting. May cause drowsiness and loss of coordination.	



Version 1.0 Version Date 12/03/2015

#### 4.6 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically.

## **5. FIREFIGHTING MEASURES**

5.1 Extinguishing media	<u>Suitable</u> : Use extinguishing agent suitable for type of surrounding fire. Avoid excessive water to minimize runoff. Prevent firefighter water from entering the environment. Small fires: Water spray, foam, dry chemical or CO2 Large fires: Water spray, fog or foam.
5.2 Special hazards arising from chemical or mixture during the fire	<ul> <li><u>Unsuitable</u>: None known.</li> <li>Container may rupture on heating. Cool closed containers exposed to fire with water spray. Do not allow run-off from firefighting to enter drains or water courses. Explosive reactions with oxidizing agents such as potassium chlorate and/or peroxides. In case of fire hazardous decomposition products may be produced such as: <ul> <li>Sulphur oxides</li> <li>Ammonia</li> <li>Carbon monoxide</li> <li>Carbon dioxide (CO2)</li> </ul> </li> </ul>
5.3 Special Protective Precautions or equipment for firefighters	In the event of fire and/or explosion do not breathe fumes. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit.

## 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment	Wear personal protective equipment.
6.2 Emergency procedures	Unprotected persons must be kept away.
	Evacuate personnel to safe areas.
	Provide adequate ventilation.
	Avoid dust formation.
	Avoid breathing dust.
	Avoid contact with skin, eyes and clothing.
6.3 Methods and materials	Do not flush into surface water or sanitary sewer system.
used for containment	Prevent further leakage or spillage if safe to do so.
	Do not let product enter drains.
6.4 Clean-up procedures	Use mechanical handling equipment.
	Clean contaminated surface thoroughly.
	Pick up and arrange disposal without creating dust.
	Use a suitable vacuum cleaner.



### 7. HANDLING AND STORAGE

7.1 Precautions for safe handling	Handle with care. Wear personal protective equipment. Use only in well-ventilated areas. Avoid dust formation. Provide exhaust ventilation if dust is formed. Dust must be extracted directly at the point of origin. Avoid breathing dust. Avoid contact with skin, eyes and clothing.
7.2 Conditions for safe storage	<ul><li>Keep containers tightly closed in a dry, cool and well-ventilated place.</li><li>Containers should be protected against falling down.</li><li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li><li>Store away from incompatible substances.</li></ul>

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ACGIH-Threshold Limit Value (TLV)

Exposure limit values of the components: Respirable crystalline silica dust: ACGIH TLV<sup>®</sup> = 0,025 mg/m<sup>3</sup> Calcium carbonate: ACGIH TLV<sup>®</sup> = 10 mg/m<sup>3</sup>

### 8.2 OSHA-Permissible Exposure Limit (PEL)

Exposure limit values of the components:

Component / CAS	TLV, 8H (OSHA, PEL)	
	mg/m <sup>3</sup>	
Quartz (SiO2)	Total dust: 30 mg/m <sup>3</sup> / %SiO2+2 (OSHA Z-3)	
CAS N°: 14808-60-7	Respirable: 10 mg/m <sup>3</sup> / %SiO2+2 (OSHA Z-3)	
	Respirable: 250 mppcf / %SiO2+5 (OSHA Z-3)	
Limestone	Total dust: 15 mg/m <sup>3</sup> (OSHA Z-1)	
CAS N°: 1317-65-3	Respirable: 5 mg/m <sup>3</sup> (OSHA Z-1)	
Particulates Not Otherwise	Total dust: 15 mg/m <sup>3</sup> (OSHA Z-1)	
Regulated (PNOR) :	Respirable: 5 mg/m <sup>3</sup> (OSHA Z-1)	

### 8.3 Any other exposure limit used or recommended by chemical manufacturer

Non applicable

### **8.4 Engineering Controls**

Provide exhaust ventilation if dust is formed. Dust must be extracted directly at the point of origin. Apply technical measures to comply with the occupational exposure limits.

### 8.5 Personal Protective Equipment

Hand protection: Gloves

Gloves must be inspected prior to use. Replace when worn.



Version 1.0 Version Date 12/03/2015

### Eye protection: Do not wear contact lenses. Wear as appropriate: Safety glasses with side-shields

### Body protection: Long sleeved clothing

<u>Respiratory protection</u>: A NIOSH approved air purifying respirator with a type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed if workplace conditions warrant a respirator use.

<u>Hygiene measures</u>: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use. Keep working clothes separately.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance (physical Multicolored granules, solid state, colour, etc.) Odour **Odourless** Odour threshold Not applicable No data available pН Melting point/freezing No data available point; **Boiling point** Not applicable **Boiling Range** Not applicable Flash point No data available Evaporation rate Not applicable Not flammable Flammability Upper/lower flammability No data available or explosive limits Oxidising properties No data available Vapour pressure Not applicable

#### Information of basic physical and chemical properties



Version 1.0 Version Date 12/03/2015

Vapour density	No data available
Density	67 lbs./ft <sup>3</sup>
Solubility in water	Partially soluble
Other Solvents	No data available
Partition coefficient (n- octanol/water)	No data available
Auto ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Not applicable

# **10. STABILITY AND REACTIVITY**

10.1 Reactivity	Not reactive under normal storage and handling condition
10.2 Chemical stability	Stable under recommended storage conditions.
10.3 Possibility of hazardous reactions	Hazardous polymerization does not occur.
10.4 Conditions to avoid	Keep at temperatures below 5374 °F (190 °C)
10.5 Incompatible materials	Strong oxidizing agents, Chlorates and Hypochlorites
10.6 Hazardous decomposition products	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Hydrogen fluoride. Hydrogen chloride. Carbon monoxide. Carbon dioxide.

## **11. TOXICOLOGICAL INFORMATION**

11.1 Measures of Toxicity		
Acute toxicity:	Ingredients:	
	Acute toxicity: N-(n-butyl)-thiophosphoric triamide (CAS 94317-64-3): LD50 Oral (Rat): > 2823 mg/kg	
Skin corrosion/irritation:	May irritate skin through mechanical abrasion	
Serious eye damage/irritation:	May cause eye irritation	



Version 1.0 Version Date 12/03/2015

Respiratory or skin sensitisation:	No data available
11.2 Listed in IARC or considered carcinogen by NTP or OSHA	Quartz (SiO <sub>2</sub> ) CAS N°: 14808-60-7 Group 1 (IARC), Volume 68, 100C
11.3 Further information	This product contains prismatic tremolite (e.g., cleavage fragments) as an impurity. Sufficient exposure to respirable prismatic tremolite dust may cause serious lung problems.

# **12. ECOLOGICAL INFORMATION**

12.1 Toxicity	May be toxic to aquatic life. In sufficient quantity may deplete oxygen required by aquatic life. May cause eutrophication of ponds and lakes.
	Potassium sulfate:
	Toxicity to fish :
	LC50: 653 mg/l
	Exposure time: 96 h
	Species: Lepomis macrochirus
	Toxicity to daphnia and other aquatic invertebrates:
	EC50: 2900 mg/l (Exposure time:72h)
	Species: Desmodesmus subspicatus (green algae)Silica:
	Toxicity to Algae and Crustacea
	IC50: 440 mg/L (Exposure time: 72 Hours)
	Species: Algae
	EC50: 7600 mg/L (Exposure time: 48 Hours)
	Species: Daphnia magna
	Carbonate calcium:
	Toxicity to fish :
	LC50: > 10000 mg/l
	Exposure time: 96 h
	Species: Oncorhynchus mykiss (rainbow trout)
	Toxicity to daphnia and other aquatic invertebrates:
	EC50: > 1000 mg/l (Exposure time: 48 h)
	Species: Daphnia magna (Water flea)
12.2 Persistence and degradability	No data available
12.3 Bioaccumulative potential	No data available



Version 1.0 Version Date 12/03/2015

12.4 Mobility in soil	No data available
12.5 Other adverse effects	May release ammonium ions that are toxic to fish. Un-ionized ammonia concentrations above 0.02 mg/l are considered toxic in fresh water. May release phosphates which will result in algae growth, increased turbidity, and depleted oxygen. At extremely high concentrations, this may be hazardous to fish or other marine organisms. Release to watercourses may cause effects downstream. Fish 96 hour LC50, OECD Guidelines 203 (rainbow trout): >86mg/L.

## **13. DISPOSAL CONSIDERATIONS**

13.1 Disposal methods to employ	Recover or recycle if possible. Properly characterize all waste materials. Consult federal, state/provincial and local regulations regarding the proper disposal of this material. Prevent material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Empty containers should be taken to an approved waste handling site for recycling or disposal.
13.2 Description of appropriate disposal containers to use	No data available
13.3 Description of the physical and chemical properties that may affect disposal activities	No data available
13.4 Language discouraging sewage disposal.	No data available
13.5 Any special precautions for landfills or incineration activities	No data available

### **14. TRANSPORT INFORMATION**

UN Number	
UN proper shipping name	
Transport hazard classes	
Packing group	
Environmental hazards	



Version 1.0 Version Date 12/03/2015

Guidance On transport in	
bulk	
Special precautions for	
user	

### **15. REGULATORY INFORMATION**

### National and/or regional regulatory information of the chemical or mixtures

Inventories:

US. Toxic Substances Control Act: No data available

OSHA Hazards: Carcinogen

<u>Clean Air Act</u>: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

### **16. OTHER INFORMATION**

#### Indications on the revision

First edition: 08/10/2015 Addition of all fields as required by regulation (US) HCS 1910.1200 [HCS 2012]. Update of the classification information and update of related sections accordingly.

#### Abbreviations and acronyms used

ACGIH: American conference of governmental and industrial hygienist CAS N°.: Chemical Abstract Service Number CFR: Code of Federal Regulations EC50: Half maximal effective concentration HCS: Hazard communication standard LC50: Half maximal lethal concentration LD50: Half maximal lethal dose OSHA: Occupational safety and health administration STOT SE: Specific target organ toxicity Single exposure STOT RE: Specific target organ toxicity Repeated exposure UN N°.: United Nations Number

### Methods of evaluation for the classification of mixtures

The classification of the mixture was set based on the regulation (US) HCS 1910.1200 [HCS 2012].

#### Other information

This information is based on our present knowledge and is provided according to the relevant national regulations. This information is intended as a characterization of the product in order to provide guidance for the relevant safety issues. However, this document does not provide any warranty, expressed or implied, regarding the properties of the product.