



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

### 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY UNDERTAKING

#### 1.1 Product identifier

Product name 28-0-10 with HydroFuze Fe

#### 1.2 Relevant use of the product

Applications Fertilizers

#### 1.3 Manufacturer, Importer or Responsible Party

Name FERTI TECHNOLOGIES  
Address 560, Chemin Rhéaume, C.P 129  
J0L 2J0  
Saint-Michel, Québec, Canada  
Telephone 450 454-7521  
Contact email astpierre@fertitechno.com

#### 1.4 Emergency phone number

Telephone USA National Capital Poison Center: 1 800 222 1222

### 2. HAZARDS IDENTIFICATION

*Hazard identification according to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200*

#### 2.1. The hazard classification of the chemical according to HazCom 2012 (US-GHS)

STOT RE 1	H372 Causes damage to organs [lungs] through prolonged or repeated exposure [inhalation].
Carc. 1A	H350 May cause cancer.
STOT SE 3	H335 May cause respiratory irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Skin Irrit. 2	H315 Causes skin irritation.

#### 2.2. Danger symbols



#### 2.3. Signal word

Danger

#### 2.4. Hazard statements

H372 Causes damage to organs [lungs] through prolonged or repeated exposure [inhalation].



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

H350 May cause cancer.  
H335 May cause respiratory irritation.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.

### 2.5. Precautionary statements

#### Prevention

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P314 Get medical advice/attention if you feel unwell.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P308+P313 If exposed or concerned: Get medical advice/attention.

#### Storage

P405 Store locked up.

#### Disposal

P501 Dispose of contents/container according to local regulations.

### 2.6. Description of any hazards not otherwise classified

Not applicable.

### 2.7. % ingredient(s) with unknown acute toxicity

Not applicable.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

	Chemical name	CAS-Nr.	Concentration %
XCU	Urea (90 % - 95 %)	57-13-6	C = 32.6 %
	Sulfur (13 %)	7704-34-9	
	Polymer coating (5 %)	n/a	



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

	Non-hazardous dye (< 0.1 %)	Proprietary	
Urea		57-13-6	C = 30.4 %
Calcium carbonate	Limestone (80 % - 100 %)	1317-65-3	C = 17.6 %
	Crystalline silica (20 %)	14808-60-7	
Potassium chloride		7447-40-7	C = 16.1 %
Oil Dri	Bentonite (90 – 100 %)	1302-78-9	C = 2.5 %
	Quartz (< 10 %)	14808-60-7	
Red iron oxide (100 %)		1309-37-1	C = 0.8 %

### 4. FIRST AID MEASURES

#### 4.1 First Aid measures after Inhalation

Following inhalation If inhalation occurs, remove affected person from area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Get medical attention if irritation develops and persists.

#### 4.2 First Aid measures after Skin exposure

Following skin contact Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Get medical attention if irritation develops and persists.

#### 4.3 First Aid measures after Eye exposure

Following eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

#### 4.4 First Aid measures after Ingestion

Following ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. If large quantities are swallowed, seek medical attention.

#### 4.5 Most important symptoms and effects, both acute and delayed

INHALATION May cause respiratory irritation. Causes damage to organs [lungs] through prolonged or repeated exposure [inhalation].  
SKIN Causes skin irritation.  
EYES Causes serious eye irritation.  
INGESTION Not classified.

#### 4.6 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically.

### 5. FIREFIGHTING MEASURES

5.1 Extinguishing media *Suitable:*



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

Use extinguishing agent suitable for type of surrounding fire. Avoid excessive water to minimize runoff. Prevent firefighter water from entering the environment.

Small fires: Water spray, foam, dry chemical or CO<sub>2</sub>

Large fires: Water spray, fog or foam.

*Unsuitable:* Not applicable.

### 5.2 Special hazards arising from chemical or mixture during the fire

Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. In case of fire hazardous decomposition products may be produced such as:

- Sulphur oxides
- Ammonia
- Carbon monoxide
- Carbon dioxide (CO<sub>2</sub>)

### 5.3 Special Protective Precautions or equipment for firefighters

In the event of fire and/or explosion do not breathe fumes. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment

Wear personal protective equipment.

### 6.2 Emergency procedures

Unprotected persons must be kept away.

Evacuate personnel to safe areas.

Provide adequate ventilation.

Avoid dust formation.

Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

### 6.3 Methods and materials used for containment

Do not flush into surface water or sanitary sewer system.

Prevent further leakage or spillage if safe to do so.

Do not let product enter drains.

### 6.4 Cleanup procedures

Use mechanical handling equipment.

Clean contaminated surface thoroughly.

Pick up and arrange disposal without creating dust.

Use a suitable vacuum cleaner.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Handle with care.

Wear personal protective equipment.

Use only in well-ventilated areas.

Avoid dust formation.

Provide exhaust ventilation if dust is formed.

Dust must be extracted directly at the point of origin.

Avoid breathing dust.

Avoid contact with skin, eyes and clothing.



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

### 7.2 Conditions for safe storage

Keep containers tightly closed in a dry, cool and well-ventilated place.  
Containers should be protected against falling down.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store away from incompatible substances.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Occupational Exposure Limits

ACGIH Nuisance dust limit of 10mg/m<sup>3</sup> (inhalable) and 3mg/m<sup>3</sup> (respirable) may apply to this product.  
Exposure limit values of the components:

### 8.2 OSHA-Permissible Exposure Limit (PEL)

Exposure limit values of the components:

Component / CAS	8H (OSHA, PEL)
	mg/m <sup>3</sup>
Quartz (SiO <sub>2</sub> ) CAS N°: 14808-60-7	Total dust: 30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 (OSHA Z-3) Respirable: 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 (OSHA Z-3) Respirable: 250 mppcf / %SiO <sub>2</sub> +5 (OSHA Z-3)
Limestone CAS N°: 1317-65-3	Total dust: 15 mg/m <sup>3</sup> (OSHA Z-1) Respirable: 5 mg/m <sup>3</sup> (OSHA Z-1)
Particulates Not Otherwise Regulated (PNOR) :	Total dust: 15 mg/m <sup>3</sup> (OSHA Z-1) Respirable: 5 mg/m <sup>3</sup> (OSHA Z-1)

### 8.3 Engineering Controls

Provide exhaust ventilation if dust is formed. Dust must be extracted directly at the point of origin. Apply technical measures to comply with the occupational exposure limits.

### 8.4 Personal Protective Equipment

Hand protection: Wear gloves and protective clothing to prevent repeated or prolonged skin contact.

Eye protection: Wear eye protection, safety glasses or goggles, to avoid possible eye contact.

Body protection: Long sleeved clothing

Respiratory protection: A NIOSH approved air purifying respirator with a type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed if workplace conditions warrant a respirator use.

Hygiene measures: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use. Keep working clothes separately.



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information of basic physical and chemical properties

Appearance (physical state, colour, etc.)	Solid
Odour	No data available
Odour threshold	Not applicable
pH	Not applicable
Melting point/freezing point;	Not applicable
Boiling point	Not applicable
Boiling Range	Not applicable
Flash point	No data available
Evaporation rate	Not applicable
Flammability	Not flammable
Upper/lower flammability or explosive limits	No data available
Oxidising properties	No data available
Vapor pressure	Not applicable
Vapor density	Not applicable
Density	58 lb/ft <sup>3</sup>
Solubility in water	No data available
Other Solvents	No data available
Partition coefficient (n-octanol/water)	No data available
Auto ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	Not applicable



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

### 10. STABILITY AND REACTIVITY

<b>10.1 Reactivity</b>	Stable under recommended storage conditions.
<b>10.2 Chemical stability</b>	Stable under recommended storage conditions.
<b>10.3 Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>10.4 Conditions to avoid</b>	Avoid heat and sunlight.
<b>10.5 Incompatible materials</b>	Strong acids, alkalis and oxidizing agents.
<b>10.6 Hazardous decomposition products</b>	If heated to the point of decomposition, carbon monoxide, carbon dioxide, oxides of nitrogen and other undefined products of organic combustion may be released.

### 11. TOXICOLOGICAL INFORMATION

<b>11.1 Measures of Toxicity</b>	
Acute toxicity:	Not classified.
Skin corrosion/irritation:	Skin contact may cause irritation.
Serious eye damage/irritation:	Eye contact may cause irritation.
Respiratory or skin sensitisation:	May cause respiratory irritation.
Chronic effects:	This product contains crystalline silica. Excessive inhalation of respirable crystalline silica may cause silicosis, a progressive, disabling and fatal disease of the lung. Symptoms may include cough, shortness of breath, wheezing and reduced pulmonary function.
<b>11.2 Listed in IARC or considered carcinogen by NTP or OSHA</b>	The international Agency for Research on Cancer (IARC), in Monograph 68 has concluded that crystalline silica inhaled in the form of quartz or cristobalite, from occupational sources is carcinogenic to humans (Group 1). The National Toxicology Program (NTP) classifies crystalline silica as a known carcinogen.
<b>11.3 Further information</b>	Not applicable.

### 12. ECOLOGICAL INFORMATION

<b>12.1 Toxicity</b>	Not classified
<b>12.2 Persistence and degradability</b>	No data available
<b>12.3 Bioaccumulative potential</b>	No data available



# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

**12.4 Mobility in soil** No data available

**12.5 Other adverse effects** Not applicable.

### 13. DISPOSAL CONSIDERATIONS

**13.1 Disposal methods to employ** Recover or recycle if possible. Properly characterize all waste materials. Consult federal, state/provincial and local regulations regarding the proper disposal of this material. Prevent material from entering sewers, storm drains, other unauthorized treatment drainage systems, and natural waterways. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**13.2 Description of appropriate disposal containers to use** No data available

**13.3 Description of the physical and chemical properties that may affect disposal activities** No data available

**13.4 Language discouraging sewage disposal.** No data available

**13.5 Any special precautions for landfills or incineration activities** No data available

### 14. TRANSPORT INFORMATION

**UN Number** .....

**UN proper shipping name** .....

**Transport hazard classes** .....

**Packing group** .....





# SAFETY DATA SHEET

## 28-0-10 with HydroFuze Fe

Version 1.0  
Version Date  
12/07/2015

**Environmental hazards** .....

**Guidance On transport  
in bulk** .....

**Special precautions for  
user** .....

### 15. REGULATORY INFORMATION

#### National and/or regional regulatory information of the chemical or mixtures

##### Inventories:

US. Toxic Substances Control Act: No data available

##### NTP, IARC, OSHA:

The international Agency for Research on Cancer (IARC), in Monograph 68 has concluded that crystalline silica inhaled in the form of quartz or cristobalite, from occupational sources is carcinogenic to humans (Group 1). The National Toxicology Program (NTP) classifies crystalline silica as a known carcinogen.

### 16. OTHER INFORMATION

#### Indications on the revision

First edition: 27/11/2015

#### Abbreviations and acronyms used

CAS N°.: Chemical Abstract Service Number

UN N°.: United Nations Number

#### Methods of evaluation for the classification of mixtures

The classification of the mixture was set based on the regulation (US) HazCom 1910.1200 [HCS 2012].

#### Other information

This information is based on our present knowledge and is provided according to the relevant national regulations. This information is intended as a characterization of the product in order to provide guidance for the relevant safety issues. However, this document does not provide any warranty, expressed or implied, regarding the properties of the product.