



25-0-5

50% UFLEXX™

Professional turf fertilizer.

Premium Turf Grade (SGN 200)

Product Features

- 50% of the nitrogen is derived from UFLEXX™ stabilized nitrogen. Stabilized nitrogen technology is the solution to nitrogen loss, ensuring optimum fertilizer efficiency while being more environmentally responsible.

Turf Benefits

- UFLEXX™ improves nitrogen efficiency, reduces nitrogen loss due to volatilization, leaching and denitrification. The result is an excellent nitrogen source with improved nitrogen efficiency which gives you an intense green color for up to 6 to 8 weeks.

Product Characteristics

Product Code:	R526666
Product Type:	Professional Turf Fertilizer
Particle Size:	Premium SGN 200
Net Weight:	50 lb
Bulk Density:	65 lb/ft ³
Coverage:	13,890 ft ² @ 3.6 lb/1000ft ² 10,000 ft ² @ 5.0 lb/1000ft ²

Guaranteed Analysis

		%
Total Nitrogen	(N)	25.0
25.0% Urea Nitrogen*		
Soluble Potash	(K ₂ O)	5.0
Chlorine not more than	(Cl)	3.7

Derived from: Urea, Potassium muriate.

*12.5% Stabilized Nitrogen from dicyandiamide and N-(n-butyl)-thiophosphoric triamide.



For more information, contact Nutrite at:

1-800-265-8865

www.nutrite.com



25-0-5

50% UFLEXX™

Directions For Use

- Read the entire label before use.
- Apply only as directed during the growing season.
- We recommend to irrigate immediately after application, especially during periods of high temperatures (80°F or above). Watering after application will accelerate initial green-up and aid the product's penetration into the turf canopy.
- Nutrite encourages responsible use of our products. Help do your part in protecting our rivers and lakes by following label indications and cleaning driveways and walkways after application. Do not apply to frozen ground.

Application Rates

Application Rate		Area Covered (ft ²)	Bags per acre	Nutrients supplied (lb/1000 ft ²)		
(lb/1000 ft ²)	(lb/acre)			N	P ₂ O ₅	K ₂ O
3.6	157	13,890	3.1	0.90	-	0.18
5.0	218	10,000	4.4	1.25	-	0.25

Suggested Spreader Settings

To provide proper distribution, calibrate spreader before application.

Rotary Spreader	Ground Speed	Width of Coverage	3.6 lb/1000ft ² Rate	5.0 lb/1000ft ² Rate
Accupro 2000	3 mph	12 ft	H ½	I ½
Scotts R-8A	3 mph	12 ft	I	J
Lesco (Letter / Numeric)	3 mph	12 ft	D /10	D ½ / 11
Earthway Rotary	3 mph	12 ft	12	13
Cyclone / Spyker	3 mph	12 ft	4	4.25
Prizelawn BF-1 / CBR III	3 mph	12 ft	G	J
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm)	4.5 mph	40 ft	5	5.75
Vicon (03 Series - Standard Spout)	4.5 mph	40 ft	20	24

Note: All of calibration starting points given above are for wheel-to-wheel coverage (100% overlap). The spreader settings should only be used for calibration starting points as age, wear and speed of spreader will impact actual applied rate.

Notice

- Information concerning the raw materials composing this product can be obtained by writing to the Guarantor listed below and referring to the item number found on this container.
- Information regarding the contents & levels of metals in this product is on the internet at <http://www.aapfco.org/metals.htm>

Precautions

- KEEP OUT OF REACH OF CHILDREN. Harmful if swallowed. Do not inhale. Fertilizer may cause irritation of eyes, nose, throat and skin. In case of contact with eyes, flush with plenty of water; get medical attention.

Storage and Use

- Store in a clean, dry place.
- Reseal opened bag by folding top down and securing.
- Use only clean, dry spreaders.
- Do not leave unused product in spreaders.

Notice to Buyer

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTY AND LIABILITY:

Buyer assumes all responsibility for safety and use not in accordance with directions. It is impossible to eliminate all risks inherently associated with the use of the product. Plant injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond seller's control. In no case shall the seller be liable for consequential, special or indirect damages resulting from the use or handling of this product.

UFLEXX® is a trademark of Koch Fertilizer, LLC.
REV1411

Manufactured & Guaranteed By:

Ferti Technologies
560 Rhéaume
St-Michel, Québec
Canada, J0L 2J0