

35-0-9

100% Polyon

Professional turf fertilizer Premium Grade (SGN 200)

Product Features

- 100% of the nitrogen is derived from Polyon polymer-coated urea.
- Phosphorus free

Turf Benefits

- Polyon slow-release nitrogen provides a long-lasting, precise and consistent feeding that lasts up to 10 weeks.
 Polyon gradually feeds for stronger and healthier turf.
- This product does not contain phosphorus. It must be used on phosphorus balanced soils or on unbalanced soils in combination with fertilizer that contains phosphorus.

Product Characteristics

Product Code:	R525791
Product Type:	Professional Turf Fertilizer
Particle Size:	Premium SGN 200
Net Weight:	25 kg
Bulk Density:	880 kg/m ³ (55 lb/ft ³)
Coverage:	18,910 ft ² @ 2.9 lb/1000 ft ² 15,310 ft ² @ 3.6 lb/1000 ft ²

Guaranteed Minimum	%			
Total Nitrogen 35.0% Nitrogen from Polymer-Coated	(N) ner-Coated Urea			
Soluble Potash	(K ₂ 0)	9.0		
Derived from: Polymer-coated urea, Muria	ate of potash			

*35.0% Slowly available Nitrogen from polymer coated urea



For more information, contact Nutrite at:

5063 North Service Rd., Suite 200 Burlington, ON Canada L7L 5H6 Toll Free: 1-800-265-8865 www.nutrite.com 560 Chemin Rhéaume St-Michel, Qc Canada JOL 2J0 Toll Free: 1-800-363-1330





35-0-9 100% Polyon

Directions For Use

- Read the entire label before use.
- Apply only as directed during the growing season.
- Irrigating after application will accelerate initial green-up.
- Nutrite encourages responsible use of our products. Help do your part in protecting our rivers and lakes by following label directives and cleaning driveways and walkways after application. Do not apply near water storm drains or drainage ditches, if heavy rain is expected or frozen ground.

Application Rates

Applica Rat		Area Covered	Bags per ha (acre)	Nutr	ients su kg/100 m (lb/1000 f	1 ²
kg/100 m ² (lb/1000 ft ²)	kg/ha (lb/acre)	m² (ft²)		N	P ₂ O ₅	K ₂ 0
1.4	142	1,760	5.7	0.50	-	0.13
(2.9)	(127)	(18,910)	(2.3)	(1.00)		(0.26)
1.8	176	1,420	7.0	0.61	-	0.16
(3.6)	(157)	(15,310)	(2.8)	(1.25)		(0.32)

Suggested Spreader Settings

To provide proper distribution, calibrate spreader before application.

Rotary Spreader	Ground Speed Width of		1.4 kg/100 m ²	1.8 kg/100 m ²	
	km/h	Coverage	2.9 lb/M	3.6 lb/M	
	(mph)	m (ft)			
Accupro 2000	5 (3)	3.6 (12)	H 1⁄2	1/2	
Scotts R-8A	5 (3)	3.6 (12)	I	½	
Lesco (Lettre / Numérique)	5 (3)	3.6 (12)	D ½ / 11	E/12	
Earthway Rotary	5 (3)	3.6 (12)	13 ½	14 ½	
Cyclone / Spyker	5 (3)	3.6 (12)	4	4.25	
Prizelawn BF-1 / CBR III	5 (3)	3.6 (12)	I	J	
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm)	7.5 (4.5)	12.2 (40)	5	5 1⁄2	
Vicon (03 Series - Standard Spout)	7.5 (4.5)	12.2 (40)	19	22	

Precautions

 KEEP OUT OF REACH OF CHILDREN. Harmful if swallowed. Do not inhale. Fertilizer may cause irritation of eyes, nose, throat and skin. In case of contact with eyes, flush with plenty of water; get medical attention.

Storage and Use

- Store in a clean, dry place.
- Reseal opened bag by folding top down and securing.
- Use only clean, dry spreaders.
- Do not leave unused product in spreaders.

Notice to Buyer

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTY AND LIABILITY:

Buyer assumes all responsibility for safety and use not in accordance with directions. It is impossible to eliminate all risks inherently associated with the use of the product. Plant injury, infectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application, all of which are beyond seller's control. In no case shall the seller be liable for consequential, special or indirect damages resulting from the use or handling of this product.

Polyon™ is a resgistered trademark of Harrell's Coatings. Rev 2012

Manufactured in Canada By:

Nutrite 560 Rhéaume St-Michel, Québec Canada, J0L 2J0

Note: All calibration starting points given above are for wheel-to-wheel coverage (100% overlap). The spreader settings should only be used for calibration starting points as age, wear and speed of spreader will impact actual applied rate.